


# ANA 217

## LINEAR FIXTURE



### KELVIN COLOR TEMPERATURE SCALE



Fixture Type: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### FEATURES

- Optional seamless lensing up to 100ft
- 100 to 1000 lumens per foot
- UL-listed for indoor applications
- Field replaceable light source
- 50,000 hour lamp life
- Dimmable to 1%
- Anodized finish

### SPECIFICATIONS

Input Voltage	24V DC / Constant Voltage
CRI	90+
Diode	Epistar
Dimming Options	PWM, Triac, 0-10V
Temp Range	-40°F to 149°F
Channel Height	37.5mm (1-1/2")
Channel Width	49mm (1-15/16")

### PART NUMBER BUILDER

Example:

**217-I-36-DV-35K-WH-SG-SV-ULV**

Model	Setting	Length (Unlimited) <sup>1</sup>	Output	CCT	Lens	Mounting	Finish	Power Supply
<b>217</b>	<b>I</b>						<b>SV</b>	<b>ULV</b>
217	I - Indoor	Inches	<b>PJ</b> - 100+lm/ft <b>PL</b> - 200+lm/ft <b>PH</b> - 300+lm/ft <b>DK</b> - 400+lm/ft <b>PQ</b> - 500+lm/ft <b>DV</b> - 700+lm/ft <b>VT</b> - 1000+lm/ft  <b>HC3RGBW</b> - Color Changing ( <i>Only available in 3K</i> )	<b>24K</b> - 2400 Kelvin <b>27K</b> - 2700 Kelvin <b>3K</b> - 3000 Kelvin <b>35K</b> - 3500 Kelvin <b>41K</b> - 4100 Kelvin <b>5K</b> - 5000 Kelvin	<b>NA</b> - None <b>WH</b> - White <b>SWH</b> - Seamless White ( <i>SWH for direct view applications only</i> )	<b>SG</b> - Spring Clip	<b>SV</b> - Silver ( <i>Custom Finishes Available</i> )	<b>ULV</b> - Universal Power Supply <sup>2</sup>

<sup>1</sup>Light Source is installed in field allowing for seamless lensing and unlimited run lengths

<sup>2</sup>120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

Conforms to ANSI/UL Standard 2108  
 Certified to CAN/CSA Standard C22.2 No. 250.0

