


BEN 228

LINEAR FIXTURE



White Lens (WH) Mounting Clips (PC) Suspension Cable (SP)



KELVIN COLOR TEMPERATURE SCALE



Fixture Type: _____

Project: _____

Location: _____

FEATURES

- Optional seamless lensing up to 100ft
- 100 to 1000 lumens per foot
- UL-listed for indoor applications
- Field replaceable light source
- 50,000 hour lamp life
- Dimmable to 1%
- Anodized finish

SPECIFICATIONS

| | |
|-----------------|---------------------------|
| Input Voltage | 24V DC / Constant Voltage |
| CRI | 90+ |
| Diode | Epistar |
| Dimming Options | PWM, Triac, 0-10V |
| Temp Range | -40°F to 149°F |
| Channel Height | 25.4mm (1") |
| Channel Width | 35mm (1-3/8") |

PART NUMBER BUILDER

Example:

228-I-48-DV-35K-WH-CP-SV-ULV

| Model | Setting | Length (Unlimited) ¹ | Output | CCT | Lens | Mounting | Finish | Power Supply |
|------------|------------|------------------------------------|--|--|--|--|--|--|
| 228 | I | | | | | | SV | ULV |
| 228 | I - Indoor | Inches | PJ - 100+lm/ft PL - 200+lm/ft PH - 300+lm/ft DK - 400+lm/ft PQ - 500+lm/ft DV - 700+lm/ft VT - 1000+lm/ft HC3RGBW - Color Changing (<i>Only available in 3K</i>) | 24K - 2400 Kelvin 27K - 2700 Kelvin 3K - 3000 Kelvin 35K - 3500 Kelvin 41K - 4100 Kelvin 5K - 5000 Kelvin | NA - None WH - White SWH - Seamless White (<i>SWH for direct view applications only</i>) | CP - Mounting Clips SP - Suspension | SV - Silver (<i>Custom Finishes Available</i>) | ULV - Universal Power Supply ² |

¹Light Source is installed in field allowing for seamless lensing and unlimited run lengths

²120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

Conforms to ANSI/UL Standard 2108
 Certified to CAN/CSA Standard C22.2 No. 250.0

