



MELISSA 006

LINEAR FIXTURE




White Lens (WH)

Mounting Clips (PC)



KELVIN COLOR TEMPERATURE SCALE



Fixture Type: _____

Project: _____

Location: _____

FEATURES

- 100 to 1000 lumens per foot
- UL-listed for indoor applications
- Field replaceable light source
- 50,000 hour lamp life
- Dimmable to 1%
- Anodized finish

SPECIFICATIONS

Input Voltage	24V DC / Constant Voltage
CRI	90+
Diode	Epistar
Dimming Options	PWM, Triac, 0-10V
Temp Range	-40°F to 149°F
Channel Height	16mm (5/8")
Channel Width	16mm (5/8")

PART NUMBER BUILDER

Example:

006-I-36-PL-35K-WH-CP-SV-ULV

Model	Setting	Length (Unlimited) ¹	Output	CCT	Lens	Mounting	Finish	Power Supply
006	I					CP	SV	ULV
006	I - Indoor	Inches	PJ - 100+lm/ft PL - 200+lm/ft PH - 300+lm/ft PQ - 500+lm/ft NRGBW - Color Changing <i>(Only available in 3K)</i>	24K - 2400 Kelvin 27K - 2700 Kelvin 3K - 3000 Kelvin 35K - 3500 Kelvin 41K - 4100 Kelvin 5K - 5000 Kelvin	NA - None WH - White	CP - Mounting Clips	SV - Silver <i>(Custom Finishes Available)</i>	ULV - Universal Power Supply ²

¹Light Source is installed in field allowing for seamless lensing and unlimited run lengths

²120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

Conforms to ANSI/UL Standard 2108
 Certified to CAN/CSA Standard C22.2 No. 250.0

